



## Cementitious Substrates

### Concrete Coatings – Primers

Products	NVM	MFFT °C	Tg °C	Properties	Applications
EPS 2532	45.0	9	-5	<ul style="list-style-type: none"><li>• Excellent efflorescence resistance</li><li>• Adhesion to ferrous and non-ferrous metals, previously painted substrates including chalky and glossy substrates</li><li>• Tannin and ink stain-blocking</li><li>• Corrosion resistance</li><li>• Flexibility</li><li>• Able to formulate &lt; 100 g/l VOC</li></ul>	<ul style="list-style-type: none"><li>• Universal primers over cementitious, wood, metal and plastic substrates</li></ul>

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.