



Air-dry/Force-dry Emulsion for Industrial and Maintenance Coatings – Selector Guide

Polymer	Primary Market	% NVM	Corrosion Resistance	Block Resistance	Early Water Resistance	Chemical Resistance	Grind Stability	Blend WR Alkyd	Starting Point VOC Capability
EPS 2506	OEM	45%	3	2	4	No	Yes	Yes	>200 g/l enamel
EPS 2550	OEM	50%	1	4	3	No	Yes	Yes	>300 g/l enamel
EPS 2535	Large OEM	45%	5	2	2	No	No	No	>240 g/l enamel
EPS 2568	OEM	40%	2	4	5	No	Yes	Yes	>300 g/l enamel
EPS 2507	Light Maintenance	48%	4	4	4	Yes	No	No	>200 g/l enamel
EPS 2548	Light Maintenance	48%	5	4	4	Yes	No	No	>100 g/l enamel

Ratings: 1 Worst - 5 Best

Questions? Call EPS Technical Service @ 1-800-601-8111

(4/08)

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.