



EMULSIONS FOR STAINS

PRODUCT	NVM	WPG	pH	MFFT	PROPERTIES	APPLICATIONS
EPS 2257	40.0%	8.80	8.0-9.0	7°C	<ul style="list-style-type: none"> ▪ All-acrylic emulsion ▪ Small particle size, excellent penetration ▪ Non-yellowing 	<ul style="list-style-type: none"> • Exterior wood and concrete stains
EPS 2293	40.0%	8.70	8.0-9.0	<10°C	<ul style="list-style-type: none"> ▪ Self crosslinking, all-acrylic emulsion ▪ Chemical resistance ▪ Abrasion resistance 	<ul style="list-style-type: none"> • Exterior clear sealers for wood and concrete

Questions? Call EPS Technical Service @ 1-800-601-8111

rev 03-01-2011

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.