



Urethane Resins for Wood Flooring & Clear Finishes

EMULSION FOR SANDING SEALER AND FLOOR VARNISH

PRODUCT	NVM	WPG	pH	Tg	PROPERTIES	APPLICATIONS
EPS 2538	40.0	8.70	10.0-10.5	30	<ul style="list-style-type: none">▪ Self crosslinking styrenated emulsion▪ Chemical Resistance▪ Wear resistant▪ Mar resistant	<ul style="list-style-type: none">• Sanding Sealer• Blend vehicle with PUD for floor finishes

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.