



Urethane Resins for Wood Flooring & Clear Finishes

EMULSIONS FOR STAINS

PRODUCT	NVM	WPG	pH	Tg	PROPERTIES	APPLICATIONS
EPS 2257	40.0	8.80	8.0-9.0		<ul style="list-style-type: none">All-acrylic emulsionSmall particle size, excellent penetrationNon-yellowing	<ul style="list-style-type: none">Exterior wood and concrete stains
EPS 2291	40.0	8.70	7.5-8.5	28	<ul style="list-style-type: none">Self crosslinking, all-acrylic emulsionChemical resistanceAbrasion resistance	<ul style="list-style-type: none">Exterior clear sealers for wood and concrete
EPS 2545	30.0	8.60		4	<ul style="list-style-type: none">Styrenated acrylic dispersionSmall particle size, excellent penetration	<ul style="list-style-type: none">Interior wiping stains

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.