



VOC REGULATIONS FOR WOOD FLOOR FINISHES & SEALERS

rev.04-21-08

AIM End Use Clear Wood Finish	Current VOC Limits			
	AIM Federal	California	OTC	SCAQMD Rule 1113
Varnish	450	350	350	275
Sanding Sealer	550	350	350	275
Lacquer	680	550	550	275
Stains (clear & semitransparent)	550	250	250	100

Exceedance Fee: Federal Regulation 40 CFR Part 59, Subpart D allows for a coatings manufacturer to produce varnishes up to 550 VOC by paying an exceedance fee. Stricter State regulations will supersede Federal Regulation and do not allow for exceedance fees.

VOC	Formulating Approaches	Recommended Products
275 g/l	<ul style="list-style-type: none"> • OMU reduced with an exempt solvent • Water-based Polyurethane Dispersion 	EPS 4431, EPS 4431/4854 blends EPS 4213
350 g/l	<ul style="list-style-type: none"> • High Solids OMU • To increase hardness (MFMA), blend 25% conventional (60% NV) OMU 	EPS 4854, EPS 4810, EPS 4627, EPS 4603 or EPS 4408
450 g/l	<ul style="list-style-type: none"> • 60% solids OMU or Uralkyd • Blends of conventional solids 50-55% solids OMU/Uralkyd with HS OMU 	EPS 4408, EPS 4603, EPS 4627
550 g/l	<ul style="list-style-type: none"> • Conventional solids Oil Modified Urethanes (OMU) and Uralkyds, • EXCEEDANCE Fee applies (Not for California or OTC) 	Above and EPS 4401, EPS 4641, EPS 4681

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.