



Urethane Resins for Wood Flooring & Clear Finishes

POLYURETHANE DISPERSIONS FOR WOOD

PRODUCT	NVM	pH	SOLVENT	VOC	TENSILE	ELONGATION	PROPERTIES	APPLICATIONS
EPS 4213	33.0	7.7-8.3	Water/NMP/TE A	205 g/l			<ul style="list-style-type: none">• Oxidizing polyurethane dispersion• Chemical & abrasion resistance• No co-solvent or driers required• Warm appearance on wood	<ul style="list-style-type: none">• Wood Floor Coating

Questions? Call EPS Technical Service @ 1-800-601-8111

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. **UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.