

## EPS® 2706

### All-Acrylic Emulsion

**MARKET SEGMENT: ARCHITECTURAL**

**COMMON APPLICATIONS: TOPCOAT**

EPS® 2706 is an all-acrylic film-forming emulsion offering excellent exterior durability and adhesion for use in exterior flat through eggshell finish house paints. EPS® 2706 offers advanced dirt pickup resistance technology to improve the brightness and appearance of exterior coatings.

#### PERFORMANCE BENEFITS

- Dirt pickup resistance (DPUR)
- Efflorescence resistance
- Grain crack resistance
- Exterior durability
- Low coalescent demand. Near-zero VOC paints can be formulated using EPS 9147 coalescent
- Made without APEO surfactants

#### TYPICAL PROPERTIES

<b>Weight Solids</b>	55.0 +/- 0.7%
<b>Weight/Gallon</b>	8.85 +/- 0.1
<b>pH</b>	8.0 – 8.5
<b>Volume Solids</b>	52.1 +/- 0.7%
<b>MFFT</b>	4° C

These typical properties do not represent specifications.

#### SUGGESTED COALESCING SOVENT(S)

(% Solvent on Binder Solids – Pass 40°F LTC Test)

<b>Texanol or EPS 9147</b>	<4%
----------------------------	-----

#### SUGGESTED FORMULATIONS

- EPS 2706 FLT1 (333-74) – Exterior Flat White/Pastel Base
- EPS 2706 FLT2 (333-75) – Exterior Flat Neutral/Clear Base